

Technical Bulletin

HUNTSMAN

JEFFCOOL® P-155 INDUSTRIAL COOLANT AND HEAT TRANSFER FLUID

GENERIC NAMES	Inhibited propylene glycol
DESCRIPTION	An inhibited propylene glycol based industrial coolant and heat transfer fluid. A slightly hazy liquid, free of suspended solids with a slight odor. A 50% by volume mixture of JEFFCOOL P-150 and deionized water.
APPLICATIONS	Since JEFFCOOL P-155 coolant is formulated with propylene glycol, it is especially suitable for applications in which toxicological and environmental considerations are critical. JEFFCOOL P-155 is a heat transfer fluid for line heaters, for snow melting systems on loading ramps, highways, and runways; a coolant for ice rinks and air conditioning (HVAC) systems.

SALES SPECIFICATIONS

<u>Property</u>	<u>Specifications</u>	<u>Test Method *</u>
Color	Red to match standard	
Water, wt.%	53.0 max.	D-1123
Specific gravity, 60/60°F	1.02 min. ; 1.04 max.	D-1122
Reserve alkalinity, ml	10.0 min. ; 14.0 max.	D-1121
pH, 33% solution	9.5 min. ; 10.5 max.	D-1287
Freezing point 100% vol., °F (°C)	-30 (-34)	D-1177

* Test methods are available upon request.

Copyright © 2005
Huntsman Corporation
JEFFCOOL® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all countries.

2034-1205

Huntsman Corporation warrants only that its products meet the specifications stated herein. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE. Products may be toxic and require special precautions in handling. For all products listed, user should obtain detailed information on toxicity, together with proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards.

Main Sales Office: Huntsman Corporation / 10003 Woodloch Forest Drive / The Woodlands, Texas 77380 / Tel: 281-719-6000 / Fax: 281-719-6416
Technical Services Section: 8600 Gosling Rd. / The Woodlands, Texas 77381 / Tel: 281-719-7780 / Fax: 281-719-7555

JEFFCOOL® P-155 INDUSTRIAL COOLANT AND HEAT TRANSFER FLUID

PRODUCT SAFETY POLICY

It is the product safety policy of Huntsman Corporation to provide our customers with information on the safe handling and use of our products. The Material Safety Data Sheet (MSDS) should always be read and understood thoroughly before handling the product, and adequate safety procedures should be followed. Information on the toxicity, environmental, and industrial hygiene aspects of our products may be found in the MSDS

HANDLING AND STORAGE

JEFFCOOL P-155 coolant may be stored in unlined carbon steel tanks and drums. If storage of concentrated JEFFCOOL P-155 coolant for periods over 12 months is desired, it is recommended that the storage vessels be constructed from aluminum, stainless steel, or lined carbon steel. Vinyl, epoxy, and phenolic linings are suitable.

The normal precautions associated with any chemical should be observed in handling JEFFCOOL P-155 coolant. This product is neither explosive nor flammable under normal storage conditions. The propylene glycol in this product is considered practically nontoxic. Splashes onto eyes or skin, however, must be washed away quickly and medical treatment is advised for eye exposure. Breathing of the vapors or mists should be avoided.

SHIPPING

JEFFCOOL P-155 coolant is available in tank wagons and 55-gallon, non-returnable steel drums. Bulk and drum inventory is available at select locations throughout the United States. Contact your local Huntsman Sales Representative for details.